

COPPER GREASE

Spanjaard Copper Grease is an antiseize compound used for the assembly of all threaded connections subject to high temperatures. Aids disassembly by preventing galling and seizing.

APPLICATIONS

- Permits firmer tightening and easier loosening of threaded connections and mating surfaces.
- Use on sparkplug threads, cylinder head and manifold studs amongst many other applications.
- Apply to the back of disc brakes to eliminate squeal.

PROPERTIES

Appearance:	Copper-brown paste
Metallic component:	Copper
NLGI consistency:	2
Typical worked penetration at 25°C (1/10 mm):	280
Max. operating temperature as a thread/antiseize lubricant (°C):	1100
Drop point:	None

DIRECTIONS FOR USE

Apply with brush/finger onto threaded connection before assembly.

PACKAGING

- 500 g plastic jar
- 5 kg plastic bucket
- 15 kg drum

Revision: 020823

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

