

## ANTI-SCUFF PASTE

**Spanjaard Anti-Scuff Paste** is a gelled, soft paste assembly compound with a high Molybdenum Disulphide (MoS<sub>2</sub>) content used for engine or parts assembly to ensure bedding in without scuffing, pick-up or scoring. Also used as an anti-seize for pipe threads and for pre-treatment of large open gears. **Anti-Scuff Spray** can be used if preferred.

### APPLICATIONS

- Reduces wear by providing lubrication during running-in.
- Use as a pre-treatment for bearings, gears, piston rings, cams, lathe centres and slides and their controls.
- Prevents seizure in nuts and bolts, valves and cocks, screw threads
- Eliminates of scuffing, pick-up or scoring.
- The presence of MoS<sub>2</sub> provides solid film lubrication up to 450°C.
- The load carrying capacity of MoS<sub>2</sub> is in excess of 2 750 Mpa (400 000 psi) .

### DIRECTIONS FOR USE

- 1) No degreasing is required before treatment, but parts should be cleaned.
- 2) Apply by hand or grease gun.

### PROPERTIES

Colour:	Black
Features:	<ul style="list-style-type: none"> <li>• Appearance: Paste</li> <li>• Worked Penetration@25°C : 265—295</li> <li>• Operating Temperature °C: -20 to 150</li> </ul>

### PACKAGING

500g tin  
5kg Tin and larger on Request



Revision: 110523

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

