

RUBBER GREASE

Spanjaard Rubber Grease lubricates all plastics and rubbers where mineral oil based lubricants aren't suitable. A vegetable oil based grease fortified with extreme pressure and anti-corrosion additives.

APPLICATIONS

- Assembly of hydraulic brake, clutch and suspension rubbers.
- Lubricates plastic or rubber components including O-rings, valves, diaphragms, cups and seals. Plastic gears and mechanisms. Swimming pool rubbers and seals. Rubber parts and cylinder rolls in train air brake systems.
- Useful in fitting rubber tubing onto components, a smear of grease inside the hose ensures effortless fitting.
- Provides lubrication where mineral oil based lubricants are not suitable.
- Compatible with all plastics and rubbers.
- Not compatible with other greases.

DIRECTIONS FOR USE

Ensure parts to be lubricated are clean and dry before application. Apply grease by brush or finger. Wipe off excess with a clean cloth.

PROPERTIES

Colour:	Translucent red.
Features:	<ul style="list-style-type: none"> • Consistency: NLGI grade 2. • Worked penetration, 25°C: 265-295 $\frac{1}{10}$th mm. • Drop point: None. • Useful temperature range: -20 - 180 °C. • Flash point: > 230 °C. • Water resistant.

PACKAGING

500 g jar



Revision: 110523

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

