

BONDFORCE WOOD GLUE

BONDFORCE WOOD GLUE is a high quality PVA adhesive for strong, reliable bonding in woodworking projects having high initial tack and excellent bond strength. It is suitable for joinery work on pine, hardwood, softwood, plywood & chipboard as well as dowel, tenon, block glueing, laminating, finger joining and veneering applications

DIRECTIONS FOR USE

1. Ensure surfaces are clean, dry and free from dust , grease and loose particles
2. Apply an even layer of glue to one or both surfaces
3. Join surfaces while glue is still wet
4. Clamp or press firmly until the bond is secure
5. Remove excess adhesive with a damp cloth before drying
6. Allow adequate drying time before handling or machining bonded parts

PROPERTIES

Appearance:	WHITE
Features:	Initial Grab: 10—15 minutes Handling Strength: 1—2 hours Full Cure: 24hours

PACKAGING

250ml, 500ml, 1L

Revision: 121223

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

