

LEAK DETECTOR

Leak Detector is specially formulated for the rapid detection of gas leaks in pressurised pipes. The product forms stable, visible bubbles at leak points, allowing for easy identification of even minor leaks. It is environmentally friendly and biodegradable, formulated to minimize environmental impact while maintaining high performance. It is non-flammable and non-toxic under normal use conditions. Safe for use on most common industrial materials.

APPLICATIONS

Applications include;

- Liquified and compressed gas cylinders
- Gas valves, regulators, and fittings
- Pipeline joints and connections
- General industrial and domestic gas systems

DO NOT USE ON:

Ammonia (NH₃) systems, Hydrogen Chloride (HCl), Sulphur Dioxide (SO₂), High-purity oxygen systems (unless certified compatible), electrical or energised equipment, frozen surfaces or sub-zero conditions.

DIRECTIONS FOR USE

1. Ensure the system is pressurised.
2. Spray the suspected leak area using a spray bottle.
3. Observe the area for bubble formation.
4. Continuous bubbling indicates the presence of a leak.
5. After testing, wipe or rinse the area if required.

PROPERTIES

Appearance	Clear Colourless liquid
Odour	Mild
Density	1.01
pH (As is)	6.0—7.0

PACKAGING

750ml Trigger



Revision: 08042026

For safety and storage information, please refer to the safety data sheet (SDS).

© Spanjaard (Pty) Ltd

ISO 9001 Certified Manufacturer

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products

748 – 750 Fifth Street, Wynberg, Sandton 2090, SOUTH AFRICA

TEL: +27 (0)11 386 7100 | EMAIL: info@spanjaard.biz | WEBSITE: www.spanjaard.biz

